The Cowboy 153 PIM

Ceiling Mount Dome Antenna





BT512600

The ideal ceiling mount antenna for transmitting & receiving in 360-degree view


- Built for Africa band ranges covering 698 MHz to 2700 MHz
- Wideband omnidirectional indoor antenna for use with signal boosting systems
- Low return loss and stable performance in a compact, lightweight design
- Up to +5 dBi gain, designed for 50 Ohm Systems
- Easy to install



ELECTRICAL SPECS			Product Specifications may change without prior notice.	
Item No.		BT512600		
Frequency Range		MHz	698-960	1710-2700
Gain		dBi	2	5
Polarization			Vertical	
Beam width	Horizontal	deg	360	
	Vertical		60	35
VSWR			≤1.8	≤1.5
PIM, 3rd Order, 2 x 20W		dBc	≤-153	
Un-Roundness		dB	±2	
Maximum Input Power		watt	50	
Impedance		ohm	50	

MECHANICAL SPECS				
Connector Type		N-Female		
Size	mm, in	203 x 98, 8.00 x 3.86		
Packing Size	mm, in	210 x 210 x 110, 8.25 x 8.25 x 4.33		
Antenna Weight	kg, lb	40, 0.88		
Packing Weight	kg, lb	45, 1.00		
Operational Temperature	°C, °F	-40 to 55, -40 to 131		
Radome Material and Color		ABS, White, RAL 7035 / Pantone 421		
Ingression Protection Rating		IP65		
Cable Length	cm, in	34, 13.38		
Coax Type		RG141		







RADIATION PATTERNS













